

PRODUCT DATA SHEET

Puridest PD 2

LAUDA Puridest stills provide ultra-pure, low-gas, sterile and pyrogen-free distillate for the dilution of reagents, sets of samples and much more besides. LAUDA Puridests purify any raw water to produce a distillate with conductivities down to below 1.6 μS .



Technical Attributes	Puridest PD 2
Ambient temperature min.	10 °C
Ambient temperature max.	40 °C
Distillation type	Mono
Material	Stainless steel
Production output	2 L/h
Conductivity at 25 °C	2.3 $\mu\text{S}/\text{cm}$
Cooling water flow rate	0.33 L/min
Dimensions (WxDxH) in mm	280x250x490
Weight	7.5 kg
Power consumption	2.0 kW

LAUDA DR. R. WOBSEY GMBH & CO. KG
Pfarrstraße 41/43 · 97922 Lauda-Königshofen
Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222
info@lauda.de · www.lauda.de
WEEE-Reg-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen
Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:
LAUDA DR. R. WOBSEY Verwaltungs-GmbH
Sitz Lauda-Königshofen
Registergericht Mannheim · HRB 560226

Geschäftsführer:
Dr. Gunther Wobser (Vors.), Dr. Mario Englert
Dr. Marc Stricker
Beirat: Dr. Gerhard Wobser